

## Specification

### Product Number(s):

95:040:200 - FBM 25 3kW  
95:040:201 - FBM 50 3kW  
95:040:202 - FBM 75 3kW  
95:040:203 - FBM 125 3kW  
95:040:204 - FBM 125 6kW

### Approvals:

BEAB and Kiwa approved to UK Water Supply Regulations.

Manufactured in the UK in a BS EN ISO 9002 registered factory.

### Capacities:

25, 50, 75 and 125 litre.

### Outer Casing:

White enamelled steel.

### Rating:

FBM:3.0kW @ 240V.

FBM:2.8kW @ 230V.

FBM:6.0kW @ 240V. (optional on FBM 125)

FBM:5.5kW @ 230V. (optional on FBM 125)

### Safety Features:

280mm (11") adjustable, manually resettable over-temperature cut-out on 3kW models. 6kW model has two manually resettable 85°C bimetallic disc-type thermal cut-outs.

### Thermal Insulation:

CFC-free polyurethane foam.

### Thermostat Spec:

280mm (11") stem-type thermostat adjustable 18°C to 70°C  
2 fitted to 6kW model.

### Water Container:

Copper heater vessel.

Polyethylene cistern tank with medium-pressure

# diaphragm-type float valve assembly to BS1212 Part 3.

**plumbworld**  
**Big brands, small prices.**

Pdf Supplied By <http://www.plumbworld.co.uk/>