

Specification

Anode:

No anode is required with this unit

Approvals:

BEAB and WRAS approved

UK manufactured in a BS EN ISO9002 registered factory

Capacities:

Model Ref. Litres kW @ 240V

A7/3 7 3

A7/1 7 1.2

A10/3 10 3

A10/1 10 1.2

Controls:

Thermostat

Capillary type, adjustable 10°C to 70°C.

Safety Cut-out

A thermal fuse cut-out is fitted in series with the adjustable thermostat.

Factory Safety:

A thermal fuse cut-out is fitted in series with the adjustable thermostat.

Guarantee:

2 year product guarantee, from date of purchase, with on-site service support. Full details are contained in the Installation Instructions supplied with each unit.

Heat Unit:

Alloy sheathed element, incorporated into an easily removable heater plate, should replacement be necessary.

Outer Casing:

The main body is substantial gauge sheet steel, anti-corrosion treated and finished in white stoved enamel. End covers are moulded in grey

high impact polystyrene. The back has three fixing points for wall mounting.

Safety Features:

A thermal fuse cut-out is fitted in series with the adjustable thermostat.

Thermal Insulation:

Approved CFC-free polyurethane foam.

Thermostat Spec:

Capillary type, adjustable 10°C to 70°C.

Water Container:

Copper. Pressure tested to 1.38 bar (20psi).

A minimum head pressure of 4 metres is required.

plumbworld
Big brands, small prices.

Pdf Supplied By <http://www.plumbworld.co.uk/>