



The Luxury Range of Air Conditioning

KYR-25CO/AG-H  
9000BTU COOL ONLY

KYR-35GW/AG-H  
12000BTU HEAT & COOL

KYR-45GW/AG-H  
14000BTU HEAT & COOL

KYR-55GW/AG-H  
18000BTU HEAT & COOL

R290  
REFRIGERANT



STERILISATION INSIDE  
**UV-C**  
DESTROYS AIRBORNE  
VIRUSES AND BACTERIA



HEAT

4



FAN




COOL

IN ONE



DEHUMIDIFY

The All New LUX Air range of Portable Air Conditioning Units features market leading technology, with the ability to Sanitize the air in the room whilst cooling or heating!




- R290 Refrigerant - Eco Friendly
- UV-C Sterilisation - High Output UV-C kills Viruses
- Wi-Fi Controllable with Tuya Smart Life Application
- Amazon Alexa & Google Assistant Voice Compatible
- A Energy Efficiency Rating (Heating and Cooling)
- SLEEP Mode - Quiet Operation for Easy Sleeping
- 12 Hour Timer Function
- Infrared Remote Control

KYR-25CO/AG-H  
KYR-35GW/AG-H  
KYR-45GW/AG-H



KYR-55GW/AG-H

\*Some specification above will not apply to all models. Please check individual specifications below



Remote Control  
Included with  
Every Unit



#### Accessories Included

- Exhaust Hose
- Unit to Hose Adaptor
- Window Slider
- Window to Hose Adaptor
- Remote Control
- Condensate Drain Tube
- User Manual
- Warranty Card

\*Exhaust Hose Extension Kits Sold Separately



| Product Code                       | KYR-25CO/AG-H   | KYR-35GW/AG-H   | KYR-45GW/AG-H   | KYR-55GW/AG-H   |
|------------------------------------|-----------------|-----------------|-----------------|-----------------|
| EAN Barcode                        | 3810025009011   | 3810035012018   | 3800450001408   | 380055000187    |
| Energy Efficiency Rating (Cooling) | A               | A               | A               | A               |
| Energy Efficiency Rating (Heating) | COOL ONLY       | A               | A               | A               |
| Power Rating (Ph/V/Hz)             | 1/220-240V/50Hz | 1/220-240V/50Hz | 1/220-240V/50Hz | 1/220-240V/50Hz |
| Cooling Capacity (BTU/hr)          | 9,000 (2.6kW)   | 12,000 (3.5kW)  | 14,000 (4.1kW)  | 18,000 (5.2kW)  |
| Heating Capacity (BTU/hr)          | COOL ONLY       | 12,700 (3.7kW)  | 16,000 (4.6kW)  | 19,000 (5.6kW)  |
| Power Input W (Cooling/Heating)    | 1000            | 1350/1391       | 1538/1520       | 2000/2043       |
| Current Input A (Cooling/Heating)  | 4.2             | 5.5 / 6.0       | 8.4 / 8.5       | 8.4 / 8.5       |
| EER (BTU/hr.w)                     | 2.9             | 2.6             | 2.3             | 2.6             |
| COP (w/w)                          | N/A             | 2.3             | 3.0             | 2.9             |
| Refrigerant Type                   | R290            | R290            | R290            | R290            |
| Compressor Brand                   | Toshiba         | Toshiba         | Toshiba         | Toshiba         |
| Dehumidification (L/hr)            | 1.0             | 1.2             | 1.5             | 1.8             |
| Noise dB(A)                        | 56              | 56              | 56              | 65              |
| Airflow (m3/hr)                    | 330             | 380             | 380             | 450             |
| Fan Speeds                         | 3               | 3               | 3               | 3               |
| Recommended Room Size (m2)         | 30m sq          | 35m sq          | 40m sq          | 45m sq          |
| Max Conservatory Size (m2)         | 15m sq          | 20m sq          | 23m sq          | 25m sq          |
| Net/ Gross Weight (kg)             | 28 / 31         | 30 / 33         | 31 / 34         | 37 / 42         |
| Net Dimension (mm) WxDxH           | 440x335x715     | 440x335x715     | 440x335x715     | 470x370x764     |
| Gross Dimension (mm) WxDxH         | 477x382x875     | 477x382x875     | 477x382x875     | 632x412x882     |
| Exhaust Hose Diameter (mm)         | 150             | 150             | 150             | 160             |
| Exhaust Hose Length (m)            | 1.5             | 1.5             | 1.5             | 1.5             |
| UV-C Lamp Voltage                  | 12V DC          | 12V DC          | 12V DC          | 12V DC          |
| UV-C Lamp Wattage                  | 0.48W           | 0.48W           | 0.48W           | 0.48W           |
| WiFi Control                       | Yes             | Yes             | Yes             | Yes             |

Please note portable air conditioning units are NOT designed to be run for 24 hours a day. These are NOT designed for server/ IT room cooling.



Tel: 0370 3344556

Web: [www.AirConditioningCentre.com](http://www.AirConditioningCentre.com)

Unit 8 Milton Business Centre, Wick Drive, New Milton, Hampshire, BH25 6RH

Email: [sales@airconditioningcentre.com](mailto:sales@airconditioningcentre.com)