



## TECHNICAL SPECIFICATION SHEET



# 100MM LOW PROFILE AXIAL FAN WITH TIMER AND BACKDRAUGHT SHUTTER

**431302**

**Slim axial extract fan with backdraught shutter and electronic overrun timer adjustable from 3 minute to 25 minutes, the factory setting is 15 minutes. Suitable for panel mounting or wall mounting using the appropriate accessory kit.**

**Key features:**

- Slim - only 15mm thick
- Suitable for wall or ceiling mounting
- High Quality ABS mouldings with external gloss finish
- Quiet Operation

**Technical specification:**

- Meets the requirements of Building Regulation Document F
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Wall 115mm
- Airflow: Panel Mount 90m<sup>3</sup>/hr

**Product range details:**

- Rated Voltage 220-240v-50Hz
- Rated Wattage 16W
- Noise Level 37.8dB(A)

**Accessories:**

- Window Kit
- Wall Kit
- External wall grille
- External gravity grille
- Ducting

**Dimensions:**

H159 x W159 x D15mm

**Fan Curves - Performance Graph**  
Low Profile Units

