

Installation Manual for LED Bathroom Mirror (Suitable for the touch switch and infrared sensor products installation by hanging bar or hardy hole)

Notes: to ensure the normal use of products, it is required set out wires as per the regulations of IEE at the installation places. The products are only applicable to be installed on the indoor. The installation must be executed by a professional electrician, wrong installation may lead to product damage and personal injury.

A / Hanging bar Installation Manual (Instruction for LED bathroom mirror) Back of the mirror Horizontal the hanging bar (1) Make a mark on the wall through the hanging bar hole and drill the holes in the mark with a drill (3) (Apply to the solid wall only) Put the expansion plug into the hole in the wall, put the hanging bar against the hole in the wall, fix the hanging Measure the distance between these two hanging bar bar in the wall with screws Please cut off all the power before the connection Brown/black Brown/red/black Yellowgreen/ green Yellowgreen/ neutral S Blue/black/white Blue/white LUMINAIRE input wiring diagram MAINS SUPPLY According to the distance, place the shorter hanging bar in 1 (6) the lower center of the longer hanging bar, then following To connect as per above photo the step 2 and step 3. Hang up the mirror Turn on the power shake left and right to see if it is stable


B / Hardy Holes Installation Manual (Instruction for LED bathroom mirror)





To connect as per above photo





Turn on the power

Function usage




"Switch " sign

- 1. Please choose below operation according to what product you buy:
- A, Touch switch.
- B. Touch switch holding to gradually dim.
- C. Touch switch press-hold color change.
- D、Tap-tap touch color change.
- E. The first short touch, turn on the light and demist pad; The second short touch, chang the color temperature; The third short touch, turn off the light and demist pad, when the light be turned on; the first holding touch; the brightness of the light can be changed from 100% to 10% or 10% to 100%, the second holding touch; the brightness of the light can be changed from 10% to 100% or 100% to 10%



Infrared sensor switch





parts list



M4 screw



D6 expansion screw



Aluminum hanging bar

Installation tools (as shown below)



Flexible rule



Leveling instrument



Churn drill



Screwdriver



Hammer

Warm tips:

- 1. Please do not use, if the product have any bocken.
- 2. During operation, never put hard and sharp materials directly against the mirror surface. Otherwise, it may result in current leakage and even personal injury accident.
- 3. Never forget to turn off the power switch in storm days. Otherwise, lightning may damage electric elements of the product.
- 4. During normal operation, never forcibly pull out the power plug to stop the product. Otherwise, electric elements of the product may be damaged.
- 5. Please pull out the power plug if the product is not used for a long time.