ALP 2HBF C

ALP Tap Range Alp 2 Hole Bath Filler Chrome



Specification				
Product Type:	Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	M16x22mm compression flexi			
Connection Outlet:	M24 Aerator			
Number of Tap Holes:	2			
Valve/Cartridge Type:	Manual			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.4 bar			
Maximum Dynamic Pressure (bar):	5.0 bar			
Maximum Hot Water Temperature °C:	60°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			
Isolation Included:	No			

Dimensions (measurements in mm)


Features:


- Long life ceramic cartridge for added durability and ease of
- Metal fixing nut for added durability
- Flexible tails included
- Minimum working pressure of

Product Certifications:



WRAS Certificate No: 2012912 WRAS Expiry Date: 31/12/2025





For more products, visit our website: http://www.bristan.com



Flow Rates (I/min)								
System Pressure (bar)	0.4	0.5	1	2	3	5		
ALP 2HBF C (mixed)	15.0	15.9	23.5	33.5	41.1	53.1		

TECHNICAL



