

BUZ SHXDIVCTFF BB

BUZZ Shower Range Buzz Adjustable Rigid Riser Diverter Bar Shower Brushed Brass



Features:

- The Buzz Bar Mixer Shower brings warm brushed brass styling to create your personal spa experience with height-adjustable overhead drenching and multi-function handset. Thermostatic controls ensure family-safe showering with preset temperature stops, while the complete kit includes everything needed for straightforward installation.
- Comes complete with a hose, height adjustable riser rail and a rub-clean anti-limescale shower rose and multi-function handset
- Control your perfect shower experience with separate flow and temperature controls for precise adjustment
- Easily fit, maintain or replace with fast-fix brackets and built-in isolation valves
- Built to last, backed by a lifetime parts and 1-year labour guarantee

Product Certifications:




WRAS Certificate No: 2301915
WRAS Expiry Date: 31/01/2028



Specification

Finish/Colour:	Brushed Brass
Main Construction Material:	ABS; Zinc Alloy
No of Controls:	2
Shower Type:	Bar Shower
Shower Head Type:	Both
Shower Kit:	Adjustable Riser with Fixed Head
Valve/Cartridge Type:	Thermostatic Cartridge & 25mm Single Lever Cartridge
Maximum Hot Water Supply Temperature °C:	60
Plumbing System Suitability:	Suitable for high pressure systems
Minimum Dynamic Pressure (bar):	1
Maximum Dynamic Pressure (bar):	5
Maximum Static Pressure (bar):	10
Connection Inlet:	1/2" Compression
Connection Outlet:	G1/2" and Riser Outlet
Isolation Valve Included:	Yes
Check Valve Included:	Yes

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	1	2	3	5
Through Handset (mixed)	6.8	10.1	12.9	16.7
Through Fixed Head (mixed)	8	11.8	14.7	19.3

TECHNICAL
DATA
SHEET



BRISTAN

D2

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.