CR SHXDIVFF C

CARRE Shower Range Carre Exposed Fixed Head Bar Shower with Diverter & Kit



Features:

- All in one box pack includes bar shower valve, hose, telescopic rigid riser rail and rub-clean anti-limescale drench head and multi function handset so nothing to buy separately
- Supplied with a fast fit Wallmount 12 fixing kit with built-in front of wall isolation valves on both the hot and cold feed, making it simple to fit, maintain and replace.
- Telescopic riser so you can adjust the height to suit your space. Giving you the flexibility to fit in a wet room/walk in shower or over a bath.
- Integral two outlet diverter so you can easily switch between the supplied handset or drench head.
- Multi function rub clean handset and drench head limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.

Product Certifications:



WRAS Certificate No: 2303902 WRAS Expiry Date: 31/03/2028

Water Label



OP QUALIA 5 CL YEARS LO ARANTE

| Specification | | | | | | |
|--|---|--|--|--|--|--|
| Finish/Colour: | Chrome Plated | | | | | |
| Main Construction Material: | Brass | | | | | |
| No of Controls: | 2 | | | | | |
| Shower Type: | Bar Shower | | | | | |
| Shower Head Type: | Both | | | | | |
| Shower Kit: | Adjustable riser with Fixed Head | | | | | |
| Valve/Cartridge Type: | 30mm Single Lever Cartridge | | | | | |
| Maximum Hot Water Supply Temperature °C: | 65 | | | | | |
| Plumbing System Suitability: | Suitable for all plumbing systems, ideally balanced | | | | | |
| Minimum Dynamic Pressure (bar): | 0.5 | | | | | |
| Maximum Dynamic Pressure (bar): | 5 | | | | | |
| Maximum Static Pressure (bar): | 10 | | | | | |
| Connection Inlet: | 15mm Compression | | | | | |
| Connection Outlet: | G1/2" and Riser Outlet | | | | | |
| Isolation Valve Included: | Yes | | | | | |
| Check Valve Included: | Yes | | | | | |

Dimensions (measurements in mm)



| 2 | Flow Rates (I/min) | | | | | | | | |
|----|----------------------------|-----|-----|------|------|------|------|--|--|
| 28 | System Pressure (bar) | 0.5 | 1 | 2 | 3 | 4 | 5 | | |
| | Through Handset (mixed) | 3.7 | 5.1 | 7.4 | 9.1 | 10.5 | 11.8 | | |
| | Through Fixed Head (mixed) | 5.3 | 8.2 | 12.1 | 15.1 | 17.5 | 19.6 | | |



Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. * - Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.