Candy

Brand

Product name / Commercial code CBG52SX Annual Energy Consumption, AEChood (kWh/a) 32.1 C Energy Efficiency class (2010/30/EC) 74.0 Energy Efficiency Index, EEI Fluid Dynamic Efficiency (FDEhood) 8.8 Fluid Dynamic Efficiency class Ε 42.0 Lighting Efficiency (Lehood) Α Lighting Efficiency class **Grease Filtering Efficiency** 72.4 Grease Filtering Efficiency class D Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h) 168 Air flow at at intensive or boost setting (m3/h) Airborne acoustical A-weighted sound power emissions at Min/Max 62 speed available in normal use (dB(A)) Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A)) Power consumption in off mode (Po) (W) Power consumption in standby mode (Ps) (W) Time increase factor, f 1.7 Measured air flow rate at best efficiency point, QBEP (m3/h) 92 Measured air pressure at best efficiency point, PBEP (Pa) 161 47 Measured electric power input at best efficiency point, WBEP (W) Nominal power of the lighting system, WL (W) 4 Average illumination of the lighting system on the cooking surface, 168 Emiddle (lux)