

**A reliable hood for clean kitchen air**

The 300 ExtractionTech Standard cooker hood efficiently removes cooking odours from your kitchen with its reliable motor. Enjoy a consistently fresh and pleasant environment every time you cook.

With its stylishly curved design in stainless steel and glass, this cooker hood will certainly make a lasting impression on your kitchen layout.

Product Benefits & Features**ExtractionTech Standard. Reliable odour extraction**

The ExtractionTech Standard hood features a reliable motor for effective odour extraction while preparing meals. Your kitchen environment remains fresh and clean for a better cooking experience, everyday.

**Light up your cooking with Pure Illumination**

Our Pure Illumination provides intense and durable lighting for full visibility while cooking. The LED lights illuminate your entire cooking surface, making it easy to see every detail of your meal preparation.

**Grease filter with reliable performance**

Experience reliable grease filtering. Designed for convenience, it can be easily cleaned by hand or in the dishwasher, ensuring your kitchen stays fresh and your hood performs at its best.

- Control type: Push buttons with 3 speeds.
- Aluminium grease filters
- Charcoal filter: This charcoal filter is used in recirculation mode to remove cooking smells. Needs replacing periodically.
- Extraction mode
- Recirculation mode
- Grease filter type and number: Aluminium mesh, 2

Product Specification

Main Colour	Stainless Steel	Max Recirculated Extraction Rate (m³/h)	245
Number of Speed Settings	3	Min Recirculated Noise Level (dB)	61
Control Type	Mechanical push buttons	Max Recirculated Noise Level (dB)	65
Lamp Type	LED spotlight	PNC	942 022 083
Energy Rating	D	Bar Code	7332543671328
Ducted Extraction Rate - Min/Max/Intensive (m³/h)	250/400/-	Net weight (kg)	13.7
Ducted Noise Level - Min/Max/Intensive (dB)	55/67/-	Gross weight (kg)	17.1
Grease Filter Efficiency Rating	C	Dimensions (mm) (HxWxD)	1020x600x500
Minimum Distance from Electric Hob (cm)	50	Installation	Chimney
Minimum Distance from Gas Hob (cm)	65	Number of Grease Filters	2
Annual Energy Consumption (kWh)	64.5	Grease Filter Type	Aluminium mesh
Size (cm)	60	Cord Length (m)	1.35
Extraction Type - Recirculation	Yes	Air Outlet (mm)	150
Extraction Type - Ducted (External)	Yes	Recommended fuse (A)	N/A
Light temperature, K	3000	Charcoal Filter	Included
Number of Lights	2	Charcoal Filter Type	ECFB01ST
Hob2Hood Connection	No	Long Life Filter Type	ECFBPL02
Fluid Dynamic Efficiency Rating	E	Super Performing Filter Type	NO
Lighting Efficiency Rating	A	OdourClean Plus Carbon filter	Not available
Min Recirculated Extraction Rate (m³/h)	175	OdourClean Pro Carbon filter	Not available

