



Geberit Sigma concealed cistern 12 cm, 5.8/3 litres



APPLICATION PURPOSES

- For drywall construction
- For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For floor-standing WCs

CHARACTERISTICS

- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting

- Flush bend fitted
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the rear or top centre
- Protection cover box for service opening protects against moisture and dirt
- Protection box for service opening can be cut to length

TECHNICAL DATA

Flow pressure	0.1–10 bar
Water temperature max.	25 °C
Flush volume, factory setting	5.8 / 3 l

Flush volume small, adjustment range	2–4 l
Product material	Plastic

INFO

- Cistern can be mounted at a lower height (98cm) as the flush pipe can be cut down.
- Flush valve features settings to enable either a 6 l and 3 l flush, 4.5 l and 3 l flush. or 4 l and 2,6 l flush . Note: must be used with pans designed for low volume flush.
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first

Art. no.	B cm	H cm	T cm
109.309.00.5	41	51	12