Installation Guide

Ideal Standard White Toilet Seat and Cover
Product reference: E002101 | Standard close | White

Before you begin

Check that the seat and cover, hinge assemblies, fixing bolts, washers, and any nuts or expansion fittings supplied are present. Remove the existing seat, and clean and dry the pan around both fixing holes. The E002101 is a standard-close seat, not a soft-close or quick-release model.

1. Prepare the hinges

Identify the two hinge fixing points on the toilet pan. Assemble the supplied hinges and washers in the order indicated by the hardware, keeping the fixings loose enough to allow adjustment. Do not substitute incompatible fixing components.

2. Attach the fixings

Position each hinge centrally over its fixing hole. For underside-access fittings, pass the bolts through the holes and fit the supplied washers and nuts from below. For expansion-type fittings, insert the supplied expansion anchors into the fixing holes and engage the screws from above. Use only the arrangement matching the fittings in the pack.

3. Position the seat

Fit the seat and cover onto the hinge posts or hinge pins as appropriate to the supplied assembly. Centre the seat over the bowl and check that the front edge follows the shape of the pan. Open and close the lid to check that neither hinge binds.

4. Tighten and check

Hold the hinges in their aligned positions and tighten the fixings evenly with the appropriate hand tool. Do not overtighten against the ceramic pan or plastic components. Check that the seat is stable and the lid opens and closes freely. Recheck the fixings after initial use.

Cleaning and care

Clean with a soft cloth, warm water, and mild soap. Rinse and dry. Avoid abrasive pads, harsh chemical cleaners, and excessive force on the hinges or lid.

Product details

White gloss urea-based plastic seat and cover. Approximate overall dimensions: 385 mm wide × 410 mm projection × 45 mm high. Standard-close hinge operation. Designed for compatible Ideal Standard White toilet pans.