Technical Data



- N° of air vents¹: 27
- · Air speed up to: 100 km/h
- Operating temperature²: 10 40 °C
- Drying time: ~ 3 minutes
- · Anti-bacterial treatment: silver ions
- Dimensions: 218 x 29,5 x 2,8 cm & 85.43 x
 11.61 x 1.1 in
- Weight: 9,8 kg
- Protection class: IP56
- Engine speed: 5000 rpm
- Voltage: 220-240 V; 50-60 Hz
- Amp: 12 A

^{1 -} Variation in temperature and speed between upper and lower vents: < 2%.</p>

^{2 -} Up to 32 °C above the ambient of temperature.

Check out our full range of Shower Enclosures

Quadrant Shower Enclosures

Corner Entry Shower Enclosures

Walk in Shower Enclosures

Sliding Shower Doors

Bifold Shower Doors

Pivot Shower Doors

Hinged Shower Doors

Shower Screens

From Top Brands

Coram Shower Enclosures

Mira Shower Enclosures

Hydrolux Shower Enclosures

Diamond Shower Enclosures

With quality shower trays to match your enclosure

Square Shower Trays

Rectangular Shower Trays

Quadrant Shower Trays

Coram Shower Trays

Mira Flight Shower Trays

