



High-performance odour removal

5000 ExtractionTech Plus ensures your kitchen air stays fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.

Product Benefits & Features

ExtractionTech Plus: High-performance odour removal

ExtractionTech Plus keeps your kitchen smelling fresh and clean every time you cook. The high-performance motor thoroughly cleans the air and removes odours for a better cooking environment.



Spotlight the details with the Pure Illumination

Energy-efficient Pure Illumination provides full visibility while cooking. The LED lights illuminate the entire cooking surface, making it easy to see every detail of your meal preparation.




Reliable, easy-to-clean grease filter keeps kitchen fresh

Convenient, reliable grease filter ensures your kitchen stays fresh and hood performs at its best. Wash by hand or in dishwasher.



Filter cleaning notification system

The hood has a convenient filter cleaning notification system. An indicator on the hood alerts you when the grease filter and carbon filter need cleaning – there's no need to keep track of it yourself.



- Air extraction capacity (high/low): 600 / 295 m³/h
- Number of speeds: 3
- Cooker hood lamps type and number: LED spotlight, 2
- Operation via push buttons
- 3 Black Aluminium mesh
- Extraction or recirculation mode possible, charcoal filter available as optional accessory for recirculation operation

Product Specification

Energy Rating	C	Intensive Recirculated Extraction Rate (m³/h)	0
Number of Speed Settings	3	Series	5000
Installation Type	Chimney	Dimensions, HxWxD	678-1180x898x450
Size (cm)	90	Frequency (Hz)	50
Extraction Type - Recirculation	Yes	Superperforming charcoal filter compatible	NO, NO
Extraction Type - Ducted (External)	Yes	Product Number (PNC)	All Open
Minimum Distance from Electric Hob (cm)	50	Plug or Hardwired	Hardwired connection only
Minimum Distance from Gas Hob (cm)	65		
Cord Length (m)	1.32		
Voltage (V)	220-240		
Required Fuse (A)	No		
Charcoal Filter Type	ECFB01		
Fluid Dynamic Efficiency Rating	D		
Lighting Efficiency Rating	A		
Grease Filter Efficiency Rating	C		
Lamp Type	LED spotlight		
Number of Lights	2		
Number of Grease Filters	3		
Min Recirculated Noise Level (dB)	62		
Max Recirculated Noise Level (dB)	73		
Min Recirculated Extraction Rate (m³/h)	250		
Max Recirculated Extraction Rate (m³/h)	415		

