



Kitchen planning freedom and flexibility

The 600 Bridge with eXtractor Hob is an induction hob with a powerful built-in extractor for greater kitchen planning freedom. And the Bridge function can combine 2 cooking zones into one large zone for cookware like planchas.

Product Benefits & Features



Merge zones for more room with the Bridge function

The Bridge function lets you combine two separate cooking zones to create a single large surface. With the temperature and time settings automatically aligned, it's ideal for making the most of planchas or roasting pots.



4 Individual Zone Controls for greater command when you cook

Easily command 4 different cooking zones and set separate timers for each with 4 Individual Zone Controls. Each zone has 9 power levels, with other functions including power boost, active touch, child lock and hob2Hood control.



The 2-in-1 Filter for fresher kitchen air

The 2-in-1 Filter includes both a charcoal and grease filter to help keep kitchen air fresh. The removable filter can be easily cleaned in the dishwasher and regenerated in the oven for prolonged use.



The extractor adjusts automatically with auto mode

Keep your mind on your cooking with an extractor that adjusts automatically as you raise or lower the power level. Auto mode extraction technology enables you to focus on your food while your hob and extractor seamlessly work for you.



Clean kitchen air quickly with the Boost function

Simply press the Boost function on the extractor for instant powerful extraction. It's activated for 10 min and efficiently cleans kitchen air from excess fumes and steam.

- Child safety lock function
- Indicator for grease filter saturation
- Indicator for carbon filter saturation

Product Specification

Nordic_Series_and_Themes	600 FLEX	Cord Length	1.5
Frame type	Bevelled 1 Side	Required Fuse	2x16
Hobs Dimensions	780x520	Total electricity loading, W	7350
Aperture dimensions HxWxD in mm	205x750x490	Voltage (V)	220-240V/400V2N
Build in type	On top	PNC	949 599 320
Air Outlet	220	EAN number	7333394040882
Filter Type	Combined Aluminium mesh		
Grease filters	2		
Charcoal filter	Included		
Radius cutting	5		
Led Colour	Red		
Energy class	A+		
Fluid dynamic efficiency class	A		
Grease filter efficiency class	B		
Left Front - Power, W / Diam., mm,	2300/3200W/210mm		
Left Rear - Power, W / Diam., mm	2300/3200W/210mm		
Right Front - Power, W / Diam., mm	1400/2500W/145mm		
Right Rear - Power, W / Diam., mm	1800/2800/180mm		
Motor Type	Brushless		
ExtractorSpeeds	3+Intensive		
Recirculation min, m3/h	250		
Recirculation intensive, m3/h	575		
Recirculation max, m3/h	465		
Recirc sound power min, dB(A)	52		
Recirc sound power max, dB(A)	67		

