N 50, Built-in double oven, Graphite
U2ACM7HG0B

NEFF

A

Double built-in oven - perfect for grilling, baking and roasting of multiple dishes at the same time.

√ CircoTherm® – Smart hot-air solution that lets you bake on up to three levels at once.

√ Dual cleaning options: Pyrolytic cleaning programmes - just let the oven interior clean itself. EasyClean - the quick and easy option for day to day maintenance.

√ LCD-Display – simple, straightforward with large characters for clear reading

√ Home Connect – Unleash your creativity via app.

√ SinglePoint MeatProbe - ensures meats are cooked perfectly every time

CircoTherm® | Pyrolysis | Wi-Fi | Singlepoint Meatprobe

Features

Technical Data

Color / Material Front : Graphite
Construction type : Built-in
Dimensions : 888 x 594 x 550 mm
Dimensions of the packed product (HxWxD) : 960 x 690 x 670 mm
Control Panel Material : Glass
Door Material : Glass
Net weight : 60.7 kg
Usable volume of cavity : 71 l
Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Full width grill, Hot Air, Hotair gentle, Hot air grilling, Pizza setting
Oven control : electronic
Number of interior lights : 1
Approval certificates : CE, VDE
EAN code : 4242004265160
Energy efficiency rating : A
Energy consumption per cycle conventional (2010/30/EC) : 1.02 kWh/cycle
Energy consumption per cycle forced air convection (2010/30/EC) : 0.81 kWh/cycle
Energy efficiency class (2010/30/EC) - cavity 2 : B
Energy consumption per cycle conventional - cavity 2 (2010/30/EC) : 0.83 kWh/cycle
Energy efficiency index (2010/30/EC) : 95.3 %
Energy efficiency index cavity 2 (2010/30/EC) : 120.3 %
Connection rating : 6300 W
Fuse protection : 32 A
Voltage : 220-240 V
Frequency : 50 Hz
Plug type : fixed connection, no plug

Included accessories

3 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0	Baking tray, non-stick ceramic coated
Z11CB10E0	Baking tray, grey enamelled
Z11CR10X0	Baking and roasting grid (standard)
Z11TF36X0	3 level telescopic rails, full ext
Z11TI15X0	Cliprails

4 242004 265160

Features

Features

- Temperature range 30 °C - 275 °C
- Cavity volume: 71 litre

Level independent telescopic rails

- 4 shelf positions
- 1 Clip rail, Stop function

Design

- Graphite-Grey Edition
- Elongated designed dials, Retractable control dials, Bevelled oval controls
- Cavity inner surface: enamel grey

Cleaning

- Pyrolytic cleaning
- EasyClean
- Full glass inner door

Programmes/functions

- LCD-display control (white)
- Electronic clock timer
- Temperature proposal
  Actual temperature display
  Heating up indicator
  Automatic start
  Temperature probe
- Bar handle
- Single-point meat probe
- Rapid heat
- Interior halogen light, On/off button
- Cooling fan
- Stainless-steel fan
- HomeConnect ready on WLAN
- 3 x combination grid, 1 x universal pan

Features

- 30 °C - Very low door temperature
- Door lock during pyrolytic cleaning
  Control panel lock
  Automatic safety switch off
  Residual heat indicator
  Door contact switch

Technical information

- Nominal voltage: 220 - 240 V
- Total connected load electric: 6.3 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A
  Energy consumption per cycle in conventional mode: 1.02 kWh
  Energy consumption per cycle in fan-forced convection mode: 0.81 kWh
  Number of cavities: Main cavity
  Heat source: electrical
  Cavity volume: 71 litre

Performance/technical information

- Appliance dimension (hxwxd): 888 mm x 594 mm x 550 mm
- Niche dimension (hxwxd): 875 mm - 888 mm x 560 mm - 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual
- We recommend you to choose complementary products within N50, in order to assure an optimal design combination of your Built-In appliances.

COOKING PASSION SINCE 1877

Dimensioned drawings

measurements in mm

20
18
888
774
8
550

Back panel open
20
19.5
145
405
875⁺¹³
min. 550
96
min. 891
180
888
60
870
20
816
max. 50
560⁺¹⁰
594
550
Space for appliance connection 320 x 115
measurements in mm