





adjustable FlameSelect control.

√ Sword Knobs - a better feel and easier to operate, the new knob in an attractive design.

The gas hob with heat-resistant ceramic glass surface and



Features

Technical Data

Product name/family: gas hob w integrated controls

Construction type : Built-in

Energy input: Gas

Total number of positions that can be used at the same time : 5

Type of control setting devices : sword knobs

Required niche size for installation (HxWxD) : 45 x 850-852 x

490-502 mm

Width of the appliance : 918 $\,$ mm Dimensions : 59 x 918 x 546 $\,$ mm

Dimensions of the packed product (HxWxD) : $165 \times 1116 \times 659$ mm

Net weight : 19.6 kg Gross weight : 22.0 kg

Residual heat indicator : without Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black, Stainless steel Color of frame : Black, Stainless steel

Approval certificates: CE, E17D UKCA marking, Eurasian

Length of electrical supply cord : 150 cm

EAN code : 4242004268758 Electrical connection rating : 1 W Gas connection rating : 13800 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz





Features

Design

- ceramic glass surface, black
- Bevelled design, stainless steel
- black cast iron pan supports with protective rubber feet
- Low profile burner: elegant burner design

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Pan supports dishwasher safe: clean without effort in the dishwasher.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left: Wok burner up to 6.1 KW (depending on gas type)
- Center front: Standard burner up to 1.9 KW (depending on gas type)
- Center rear: Economy burner up to 1.1 KW (depending on gas type)
- Right rear: High speed burner up to 2.8 KW (depending on gas type)
- Right front: Standard burner up to 1.9 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
 NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU)
 Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar
 Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 59 x 918 x 546
- Required niche size for installation (HxWxD mm): 45 x 850 x (490 502)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 13.8 KW

Accessories

• 1 x WOK attachment ring included