

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B



D

LZ00XXP00	Long Life odor filter (replacement)
LZ10FXJ00	Long Life recirculation kit
LZ11DXB14	Clean Air Standard odor filter (repl.)
LZ11DXI14	Clean Air Standard recirculation kit
LZ11DXI16	Clean Air Plus recirculation kit
LZ11FXC56	Clean Air Plus recirc. kit external
LZ11FXD51	Long Life recirculation kit external
LZ12250	Chimney extension 1000 mm
LZ12350	Chimney extension 1500 mm
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ50960	Backboard 90x65cm
LZ50961	Backboard 90 x 72 cm

Box design extractor hood with high extraction rate.

✓ Illuminate your cooking space with LED lights for optimal visibility and ambience setting.

Typology: Wall-mounted
Length electrical supply cord: 130.0 cm
Height of the chimney: 583-912/583-1022 mm
Height of the appliance: 53 mm
Minimum distance above an electric hob: 550 mm
Minimum distance above a gas hob: 650 mm
Weight: 12.8 kg
Control panel: mechanical
Number of speed settings: 3
Maximum output air extraction: 365 m³/h
Maximum output recirculating air: 240 m³/h
Maximum Air flow: 365 m³/h
Number of lights: 2
Noise level: 64 dB(A) re 1pW
Diameter of air outlet: 120 / 150 mm
Grease filter material: Washable aluminium
EAN code: 4242003811184
Connection Rating: 100 W
Fuse protection: 10 A
Nominal power: 220-240 V
Frequency: 50; 60 Hz
Plug type: GB plug
Installation type: Wall-mounted

4 242003 811184

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel LC94BBC50B

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 365 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- 3 x metal grease filter cassettes - dishwasher safe
- Installation: wall

Design

- Chimney hood
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Maximum extraction rate exhaust air 365 m³/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use:240m³/h
- Noise level in recirculation mode: Max. normal use:65 dB(A) re 1 pW
- Power rating: 100 W
- Light Intensity: 91 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 500 mm
- Dimensions recirculating, chimney (HxWxD): 635-1075 x 900 x 500mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 900 x 500mm - mounting with outer chimney
- 833-1163 x 900 x 500 mm - mounting with telescopic chimney
- Blower Efficiency Class: E*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 53.1 kWh/year*

Optional accessories

- Recirculating kit LZ00XXP00

* In accordance with the EU-Regulation No 65/2014

iQ100, Wall-mounted cooker hood, 90 cm, Stainless steel
LC94BBC50B

