

Mira Minimal Dual Outlet

Mixer Shower



SUITABLE FOR MAINS
UNVENTED AND
COMBI-BOILERS



5 YEAR WARRANTY

Mira Minimal is a thermostatic, mixer shower specifically designed to improve water efficiency. With patented technology, to optimise performance, delivering an enhanced showering experience at 8 LPM.

Product Information

Description	Colour	Product No.
Mira Minimal Dual	Chrome	39451W-CP
Mira Minimal Dual	Black	39585W-BL

Features & Benefits

Temperature control

Thermostatic temperature stability

Easy to fit

Pipe centers 50 mm apart

Spanner free installation

Pipe spacer guide included to aid pipework installation during first fix

Front of tile installation system allows connection to pipework during second phase fix after tiling is complete

Multi-use tool supplied to aid installation

For your customer

On/off single sequential control for flow and temperature

Maximum temperature stop for increased safety (with override for a hotter shower)

Lever diverter control allows water to be diverted to either the shower handset or shower overhead

Mira Cool Shield™ to ensure valve doesn't get hot during showering

Variable spray 10 cm showerhead with rub clean nozzles

Large 20 cm anti drip deluge showerhead with rub-clean nozzles

1.25 m flexible shower hose



Product Specification

Tech Details

Temperature and flow control

Temperature control type: Thermostatic

Flow control type: On/off single sequential cartridge

Installation

Water entry points: Rear only

Inlet connections: Direct 15 mm push fit connections

Outlet connections: ½" BSP Male

Reversed inlets supported: No = hot left, cold right only

Supply Conditions (hot and cold)

Cold water range: 1 °C to 25 °C

Hot water range: Min 55 °C; 60 °C - 65 °C (recommended)

Minimum maintained pressure: 1 bar (10 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at showerhead): 8 l/min

Flow rate (at deluge head): 8 l/min

Product factory restricted to 8 l/min

Temperature stability: ± 2 °C

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp

Adjustable maximum temperature for on-site conditions

Approvals

KIWA UK approved product

WRAS approval pending (Water Regulations Advisory Scheme)



Dimensions

