


N 70, GAS HOB, 60 CM, STAINLESS STEEL  
T26CIH8N0



The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- ✓ FlameSelect®: Gain precise control of your flame.
- ✓ Metallic Sword Dial: Precise and removable for easy cleaning.
- ✓ Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- ✓ Wok Burner: Powerful cooking at up to 3.5 kW.
- ✓ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

Z1365WX0	Wireless food thermometer
Z2402X0	Small pot support
Z2471X0	Wok ring
Z2480X0	Simmer plate
Z9404SE0	4 pieces Set
Z9406SE0	6 pieces Set

Product name/family: .....gas hob w  
integrated controls  
Built-in / Free-standing: ..... Built-in  
Energy input: ..... Gas  
Number of cooking zones: ..... 4  
Required niche size for installation (HxWxD): ..... 45 x 560-560 x  
480-490 mm  
Width of the appliance: ..... 582 mm  
Dimensions: ..... 51.5x582x520 mm  
Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm  
Net weight: ..... 10.8 kg  
Gross weight: ..... 12.0 kg  
Residual heat indicator: ..... Separate  
Location of control panel: ..... Front  
Basic surface material: ..... Stainless steel  
Color of surface: ..... Stainless steel  
Length electrical supply cord: ..... 100.0 cm  
EAN code: ..... 4242004284536  
Gas connection rating: ..... 8000 W  
Fuse protection: ..... 3 A  
Voltage: ..... 220-240 V  
Frequency: ..... 50; 60 Hz



## N 70, GAS HOB, 60 CM, STAINLESS STEEL T26CIH8N0

### Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet
- full metal

### Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

### Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

### Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

### Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.5 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 8 KW

