

N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27PIQ4S0



Z1365WX0 Wireless food thermometer
Z2402X0 Small pot support
Z2471X0 Wok ring
Z2480X0 Simmer plate
Z9404SE0 4 pieces Set
Z9406SE0 6 pieces Set

The gas hob with precise flame control, removable dials and semi-continuous pan supports that are suitable for dishwashers for Comfort Clean.

- $\sqrt{\text{FlameSelect}^{\otimes}}$: Gain precise control of your flame.
- $\sqrt{}$ Metallic Sword Dial: Precise and removable for easy cleaning.
- $\sqrt{}$ Cast Iron Pan Supports: Maximum stability, easy handling, and dishwasher cleaning.
- $\sqrt{}$ Wok Burner: Powerful cooking at up to 4 kW.
- $\sqrt{\ }$ Gas Safety Cut-Off: Safety first! No flame, no gas flow.

Product name/family:	gas hob w
integrated controls	
Built-in / Free-standing:	Built-in
Energy input:	
Number of cooking zones:	
Required niche size for installation (HxWxD):	
480-492 mm	
Width of the appliance:	752 mm
Dimensions:	
Dimensions of the packed product (HxWxD): .	
Net weight:	
Gross weight:	
Residual heat indicator:	~
Location of control panel:	
Basic surface material:	
Color of surface:	
Color of frame:	
Length electrical supply cord:	
EAN code:	
Gas connection rating:	
Fuse protection:	
Voltage:	
Frequency:	
rrequericy.	



N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27PIQ4S0

Design

- tempered glass surface, black
- Two built-in options:
- - Flush installation Surface mounted installation: install the hob either flush or slightly raised on the worktop
- Cast iron pan supports with rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 4 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.
- Cast iron pan supports with rubber feet: little weight and compact form, yet high stability due to continuous surface.

Safety

• Flame failure safety device: prevents unwanted gas flow when flame

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 54 x 752 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- \bullet If installed flush, minimum worktop thickness is 30mm.
- Power cord: 1 m
- Connected load: 11.5 KW



N 70, GAS HOB, 75 CM, TEMPERED GLASS, BLACK T27PIQ4S0

