

## N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8NO



The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- $\sqrt{\text{FlameSelect}^{\text{@}}}$ : Gain precise control of your flame.
- $\sqrt{\,}$  Metallic Sword Dial: Precise and removable for easy cleaning.
- $\sqrt{}$  Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- $\sqrt{\,}$  Dual Wok Burner up to 5.0 kW: Use one gas flame for simmering, two for sizzling stir-fries.
- $\sqrt{\mbox{ Gas Safety Cut-Off: Safety first!}}$  No flame, no gas flow.

Z1365WX0 Wireless food thermometer Z2402X0 Small pot support

 Z240ZX0
 Small pot Support

 Z2471X0
 Wok ring

 Z2480X0
 Simmer plate

 Z9404SE0
 4 pieces Set

 Z9406SE0
 6 pieces Set

Product name/family:	aas hob w
integrated controls	······································
Built-in / Free-standing:	Built-in
Energy input:	Gas
Number of cooking zones:	5
Required niche size for installation (HxWxD):	45 x 850-852 x
490-502 mm	
Width of the appliance:	
Dimensions:	51.5x915x520 mm
Dimensions of the packed product (HxWxD):	165 x 1116 x 659
mm	
Net weight:	16.0 kg
Gross weight:	9
Residual heat indicator:	
Location of control panel:	
Basic surface material:	
Color of surface:	
Length electrical supply cord:	
EAN code:	
Gas connection rating:	
Fuse protection:	
Voltage:	
Frequency:	50; 60 ⊓2



## N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8NO

#### Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet
- full metal

#### Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

### Burners and power

- 5 burner hob
- Including 1 wok burner: use an extra wide power range, separately controlling two flame rings.
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 5 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

#### Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

#### Safety

 Flame failure safety device: prevents unwanted gas flow when flame goes out.

#### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.5 x 915 x 520
- Required niche size for installation (HxWxD mm) : 45 x 850 x (490 502)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 12.5 KW

#### Accessories

ullet 1 x WOK attachment ring included



# N 70, GAS HOB, 90 CM, STAINLESS STEEL T29CIR8NO

