



## Traditional Heated Towel Radiator 952 x 479mm

A traditional floorstanding heated towel radiator combining a chrome steel frame with crisp white column detailing. Designed for central-heating systems, it provides both room heating and practical towel warming in a compact period-style design.

### Product Specifications

| Specification                       | Details                           |
|-------------------------------------|-----------------------------------|
| Brand                               | Park Lane                         |
| Product type                        | Traditional heated towel radiator |
| Fuel type                           | Central heating                   |
| Orientation                         | Vertical / floorstanding          |
| Height                              | 952 mm                            |
| Width                               | 479 mm                            |
| Depth                               | 235 ± 5 mm                        |
| Projection                          | 153 mm                            |
| Projection from wall incl. brackets | 54 mm                             |
| No. of rails                        | 4                                 |
| Material                            | Steel                             |
| Finish / colour                     | Chrome with white columns         |
| Weight                              | 11.2 kg                           |
| Heat output $\Delta T30$            | 212 W / 723 BTU                   |
| Heat output $\Delta T50$            | 406 W / 1,386 BTU                 |
| No. of connections                  | 2                                 |
| Maximum working pressure            | 6 bar                             |
| Water temperature range             | 40–95°C                           |
| Guarantee                           | 10 years                          |

### Key Features

- Traditional Victorian-inspired styling
- Floorstanding installation
- Four towel rails
- 406W / 1,386 BTU heat output at  $\Delta T50$
- Pressure tested to 13 bar
- Suitable for central-heating systems
- 10-year guarantee

### Installation Notes

Radiator valves are required separately. Published retailer information currently gives conflicting tapping/tube-centre measurements, so pipe centres should be confirmed from the supplied technical drawing or the physical radiator before pipework is permanently positioned.