INSTALLATION GUIDE

Moon soft-close toilet seat and cover | White | YFG108C

Installation overview

This guide describes the general top-fix installation sequence for the YFG108C seat. Use the exact washers, anchors, and fasteners supplied with the product; hardware configurations may vary.

1. Check components

Unpack the seat, cover, hinge assemblies, and supplied fixing hardware. Check that the hinges and fixings match the WC pan and that no parts are damaged.

2. Prepare the pan

Remove the existing seat, if fitted. Clean and dry the mounting area around the two fixing holes.

3. Position the hinge fixings

Place the supplied top-fix hinge assemblies at the pan mounting holes. Fit the washers, anchors, and fasteners in the arrangement supplied with the seat hardware.

4. Align the seat

Position the seat on the hinges. Centre it over the pan and check that the front and sides align correctly and that the lid moves freely.

5. Secure the hinges

Tighten the fixings evenly, using hand tools and avoiding overtightening. Ensure the hinges are secure and the seat does not shift.

6. Test operation

Open and close the seat and lid to check soft-close movement. Test the quick-release button and refit the seat securely after cleaning.

Cleaning and maintenance

Release the seat using its quick-release control when cleaning around the hinges. Wipe with mild soapy water, dry with a soft cloth, and refit until secure. Do not force the soft-close mechanism.