

Sentinel X200 Noise Reducer

Non-acidic leave-in treatment to cure boiler noise

Sentinel X200 Noise Reducer is a non-acid product that has been formulated for the treatment of “kettling” in central heating boilers.

- **Speciality ingredients**
Eliminate micro-boiling that causes boiler noise
- **Fights scale build up**
Helps maintain boiler efficiency
- **Leave in treatment**
Long lasting prevention of boiler noise



The Sentinel System

Lifetime protection for heating and hot water systems using the best practice process of...



CLEAN
WITH
APPROPRIATE
CLEANER



PROTECT
WITH X100
INHIBITOR



MAINTAIN
WITH
TEST KIT

Application

Sentinel X200 is a non-acid product that has been formulated for the treatment of 'kettling' in central heating boilers caused by limescale. Unlike alternative treatments, Sentinel X200 is added to the system and left there without causing any problems. Sentinel X200 is extremely successful in reducing noise problems caused by the presence of limescale on the heat exchanger surface, and restoring boiler efficiency. Many noise problems are caused by system design or mechanical faults; it is important to check for these before seeking a chemical solution.

Dosing

1 litre of Sentinel X200 is sufficient to treat a typical domestic system of 8 to 10 radiator panels. Larger systems should be dosed with 2 litres. The time taken for boiler noise to reduce or be entirely eliminated will depend on the hardness and quantity of limescale present. In severe cases, a further dose of Sentinel X200 may be necessary. Sentinel X200 should be left in the system. The system water should also be treated with Sentinel X100 inhibitor, or Sentinel X500 Inhibited Antifreeze.

Open Systems: Dose via F&E cistern, via a by-pass feeder or use a Sentinel Dosing Vessel.

Sealed Systems: If the system is empty, add to any convenient point before filling.
If full, use a Sentinel Dosing Vessel to inject via the filling loop or other access point.

Physical properties

Appearance: Clear colourless liquid

Specific gravity: 1.02 (20°C)

pH in aqueous solution (1%) 7.5 (approx)

Freezing point: -1.5°C

Safety precautions

The information provided below enables compliance with the Control of Substances Hazardous to Health Regulations. A full Safety Data Sheet is available upon request.

Boiler Noise Reducer for Central Heating Systems An aqueous solution of speciality ingredients.

Health hazards	Not for use in potable water systems. Not considered hazardous to health.	
Handling	Avoid contact with skin and eyes. Keep out of reach of children and animals. Wash out empty container thoroughly with water before disposal.	
Storage	Keep container tightly closed. Store in cool, well ventilated area.	
Spillage	Flush spillage with plenty of water and wash to waste.	
Fire/explosion risks	Non-flammable	
First aid	Skin Exposure:	Wash immediately with plenty of water. If irritation develops, seek medical attention.
	Eye Exposure:	Flush immediately with plenty of running water. Keep eyelids apart. Seek medical advice.
	Ingestion:	Rinse mouth with water. Do NOT induce vomiting! Seek medical advice.

We're proud to be endorsed by the industry's major international manufacturing companies:



Sentinel Performance Solutions Ltd

7650 Daresbury Park, Warrington, Cheshire, WA4 4BS, United Kingdom.

Tel: +44 (0)1928 704 330 www.sentinelprotects.com



Check out our full range of Heating Products

Central Heating Controls

Honeywell Heating Controls

Danfoss Heating Controls

Radiator Valves

Fernox

Sentinel

Magnaclean

Warmup underfloor heating

Water Heaters

Hand Dryers

plumbworld
Big brands, small prices.