# SMEDBO | DRY

INSTALLATION & OPERATING GUIDE • FK717

**Four Arm Electric Towel Rail**
Polished Stainless Steel | Product code: SMEDFK717

| | | | |
|---|---|---|---|
| Height | 777 mm | Arm length | 403 mm |
| Depth | 87 mm | Cord length | 1400 mm |
| Supply | 220–240 V AC / 50 Hz | Protection | Class I / IP44 |
| Rated power | 40 W (product specification) | Finish | Polished stainless steel |

## Before installation

Read these instructions fully and retain them for future reference. Check the towel rail and cable for damage before fitting. Do not install or use a damaged appliance.

Electrical work in bathrooms, including a concealed/hardwired connection, must be carried out by a qualified electrician in accordance with applicable regulations. The electrical supply must match the appliance rating.

## Wall mounting

**1.** Choose a suitable solid wall position and check for concealed cables and pipes. The lowest heated connection point must be at least **600 mm above finished floor level**. Locate the rail so its switch and electrical connections cannot be reached by someone in the bath or shower.

**2.** Prepare the rail mounting assembly and offer the unit up to the wall. Check it is vertical and that all four swivel arms can move freely without striking adjacent fittings.

**3.** Mark the fixing positions using the actual rail/brackets as a template. Check alignment and the wall substrate before drilling.

**4.** Drill appropriate holes and fit wall plugs/anchors suitable for the wall material. Use the supplied fixing hardware where suitable. Do not drill into concealed services.

**5.** Secure the mounting fixings and place the rail onto the brackets. Tighten the retaining grub screws with the appropriate Allen key. Check that the unit is secure and that its arms swivel correctly.

## Electrical connection

For the supplied cable and plug, use only a suitably located, compliant electrical outlet. Do not position the plug or socket where it may be exposed to water.

For a concealed fixed electrical connection, the compatible **FK725 mounting kit** is required. Installation must be completed by a qualified electrician, with appropriate all-pole isolation and protective measures. Do not attempt to modify the cord or connection yourself.

IP44 protection does not remove bathroom zoning requirements. Confirm the permitted installation location under current UK wiring regulations.

## Operation and care

Use the appliance switch to turn heating on or off. The surface may become hot during operation; avoid prolonged skin contact. The appliance incorporates over-temperature protection.

Designed only for drying textiles dampened with water. Do not cover the appliance with unsuitable materials or use it outdoors. Disconnect/isolate power and allow to cool before cleaning; wipe with a soft damp cloth, then dry. Never immerse in water.

Children must not play with the appliance. Children aged 8 and over and people requiring assistance may use it only with appropriate supervision or instruction.

## Safety checks

Before first use, confirm the rail is firmly mounted, fixings are secure, the cable is undamaged, and the electrical installation is compliant. If the cord is damaged, arrange replacement by a qualified professional.