

Eastbrook Thermostatic Radiator Valve (TRV)



Thermostatic valves are typically used for regulating the fluid flow to the radiators of central heating systems. They are provided with a regulating element which automatically controls the opening of the valve to keep the ambient temperature of the room where they are installed constant at the set value. The number on the valve corresponds to a specific air temperature. Once you have selected a number, the thermostatic valve will maintain this temperature. This prevents unwanted temperature rises and achieves considerable energy savings. The quality is up to the requirement of EN 215 standard.

TECHNICAL SPECIFICATION:

- With thermostatic head and reversible bi-directional body.
- Built-in sensor with liquid-filled element
- Graduated scale from 0 to 5 corresponding to temperature setting ranges from 6°C - 28°C with frost protection setting as well (As per Figure below)
- Fully tested to 10 bar
- Max pressure difference: 0.1 Bar
- Nominal flow rate 173L/h
- Max flow temperature 100°C
- Can be mounted horizontally or vertically

6°C	11-13°C	15-17°C	19-21°C	23-25°C	27-28°C
*	1	2	3	4	5

IMPORTANT NOTE : Read all instructions before commencing work. This product should only be fitted by a fully qualified installer.

Eastbrook 

Eastbrook Road, Gloucester GL4 3DB

Technical Helpline : 01452 317890

Mon - Fri / 8am - 5pm

Email : technical@eastbrookco.com