

Xpelair Simply Silent Contour Range



Simply Silent Contour Range



- Silent intermittent fan with 2 speeds
- Suitable for wall, ceiling, window and panel mounting
- Quiet Mark pending
- Fresh white appearance, available in square or round options
- Easy to install and replace existing fans
- 2 year guarantee on product
- IPX4 rated
- Meets Building Regulations Part F

Part Number	Description	Square Fan	Round Fan
92960AW	C4S Simply Silent Extract Fan	✓	
92961AW	C4R Simply Silent Extract Fan		✓
92962AW	C4TS Simply Silent Extract Fan	✓	
92963AW	C4TR Simply Silent Extract Fan		✓
92964AW	C4PS Simply Silent Extract Fan	✓	
92965AW	C4PR Simply Silent Extract Fan		✓
92966AW	C4HTS Simply Silent Extract Fan	✓	
92967AW	C4HTR Simply Silent Extract Fan		✓

Simply Silent Contour CV Range



- Constant volume fan
- Integral hour-run timer
- Suitable for wall, ceiling, window and panel mounting
- Quiet Mark pending
- Fresh white appearance available in square or round options
- Easy to install and replace existing fans
- Low running costs
- 5 year guarantee on motor
- Meets Building Regulations Part F
- Low volt version specifically designed to be installed directly in or over the splash area zone 1 in complete safety. Product supplied with a 12V SELV transformer which is sited out of reach of any person using the bath or shower

Part Number	Description	Square Fan	Round Fan
92968AW	CV4S Simply Silent Extract Fan	✓	
92969AW	CV4R Simply Silent Extract Fan		✓
92970AW	LVCV4S Simply Silent Extract Fan	✓	
92971AW	LVCV4R Simply Silent Extract Fan		✓

Ghost™ Airflow Technology

- Flow straighteners to guide air through duct, reducing turbulence thus making flow laminar
- Cone reduces turbulence in front of fan. Air is directed straight into the impeller
- Ball-bearing motors to suppress noise from motor (contour)
- Low watt motors



Xpelair Simply Silent Contour Range



Installation

- Strengthened duct to avoid breakage at install. Also reduces duct distorting on fitting and fouling impeller
- Circular back plate allowing 3 screws vs conventional 4 on most fans – 25% time saving at install
- Radial screw slots to allow movement and alignment of back plate before fixing final screw
- Level line at bottom of back plate for ease of alignment
- Large cable access for ease of wiring
- Easy to remove / replace front access cover:
 - Notch to remove cover with tool – no screws!
 - To replace hook at top, rotate, press and clip back into place
- Twist and turn baffle for removal for ease of cleaning



Dimensions

