



**011-2014**

1. Unique identification code of the product

**EASY**

2. Intended use/es:

**In heating systems in buildings**

3. Manufacturer

**TERMA Sp**

**Email: [terma@termagroup.pl](mailto:terma@termagroup.pl)**

4. System/s of AVCP:

**System 3**

5. Harmonised standard:

**EN 442-1:2014**

7.

Essential characteristics	Properties	Harmonised technical specification
Reaction to fire	A1	EN-442-1:2014
Release of dangerous substances	No releases	
Pressure tightness	No leakage at 1,3 x maximum MOP	
The surface temperature	Max. 95°C	
Resistance to pressure	No breakage at 1,69 x MOP Maximum operating pressure (MOP): 800kPa	
Rated thermal output	Table 1	
Thermal output in different operating conditions (characteristic curve)	$\Phi = K_M \cdot \Delta T^n$ , K <sub>M</sub> i n see Table 1	
Trwałość jako: Durability as:		
Resistance against corrosion	Absence of surface corrosion after 100 h humidity	
Resistance against minor impact	Class 0	

Name	Hight	Width	Output $\Delta T=50^{\circ}\text{C}$	Output $\Delta T=30^{\circ}\text{C}$	$K_M$	n
[-]	[mm]	[mm]	[W]	[W]	[-]	[-]
EASY	640	200	124	68	1,1956	1,1865
EASY	960	200	187	102	1,7740	1,1906
EASY	1280	200	251	136	2,3038	1,1990
EASY	1600	200	314	170	2,8300	1,2038
EASY	1920	200	378	204	3,3533	1,2080

The performance of the product identified above is in conformity with the set of declared performance/s.  
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Patrycja Kopczyńska**

